TECHNICAL DATA SHEET



OB1 All Weather Repair Tape Extreme Strength Clear



Clear 50mm x 20m

Product Description:

OB1 All Weather Repair Tape Extreme Strength is a crystal clear structure repair tape indended for repair, assembly covering and protecting of clear/transparent objects such as glass, plastic or film.

Application:

Used for for sealing of broken or punctured surfaces where transparency and resistance to elements are imperative. Suitable for repair of glass surfaces (windows, furniture, headlights, taillights, windshields), as well as for plastic greenhouse covers. Not suitable for PE and PTFE.

Usage Guidelines:

Upon application, the treated surface must be clean and free from dust and grease. Avoid touching the exposed adhesive surface in order to keep full adhesive performance. Firm hand pressure is recommended for 30 seconds, ensuring to press out any air bubbles for optimal bonding. Can be used after 2hrs, maximum strength after 24hrs. **Not for use as an electrical tape.**



TECHNICAL DATA SHEET

Carrier	LDPE film	
Color	Transparent	
Adhesive	Water acrylic	
Total thickness	150mic +/- 5mic	
Initial tack	17	
Peel adhesion	>34.5N/cm	
Tensile strenght	82.5N/cm	
Elongation	550%	
UV resistant	Yes	
High heat resistance	10°C-100°C	
Water resistance	Waterproof	
Low odor	Yes	
Chuck material	Cardboard	
Chuck outer diameter (mm)	76.4	
Tape width	50mm	
Tape length	20m	
Box quantity	20	

Storage:

Store in a clean, dry area without direct sun exposure and with good ventilation. Preferable storage temperature is between 10°C and 30°C.

Health & Safety

Product Safety Data Sheet must be read and understood before use.

These are available on request and via our websites

Warranty & Guarantee

Bostik warrants that its product complies, within its shelf life, to its specification.

Disclaimer

All information in this document and in all our other publications (including electronic ones) is based on our current knowledge and experience and is the exclusive (intellectual) property of Bostik. No part of this document may be copied, shown to third parties, reproduced, communicated to the public



ISO 14001:2015 | ISO 9001:2015 | ISO45001:2018