

# König PREMIUM Edge Pen

243 000

## Intended Use

- For the opaque colouring of closed surfaces in the wood, plastic and metal sector.
- For a quick uncomplicated colouring of corners, edges and grooves.
- For the touch-up of flaws.
- For indoor and outdoor use.

## Characteristics

- Pigmented, acrylic-based covering lacquer.
- Dries rapidly.
- High opacity.
- Overcoatable with all König touch-up and spray lacquers.
- Good adhesion to many lacquer, plastic and metal surfaces (not to Soft-PVC).
- Limited PVC resistance (window and door gaskets).
- Good lightfastness and weather-resistance.

## Application Notes

The parts to be coloured must be dry and free of dust, silicone and grease.

Prior to each use, shake pen for about 30 seconds. Rattle of mixing balls must be clearly heard. Due to exterior influences (heat), an overpressure may develop in the pen. To prevent blotching during activation or pumping, the pen must be de-aerated. Take off cap and hold pen with tip pointing upwards (preferably in a cloth). Pen is audibly de-aerated by briefly squeezing area marked 'P'.

Hold pen with tip pointing downwards and press slightly until tip is soaked with dye. Touch-up with rapid strokes. When used in outdoor environments, it is vital to apply thicker layers of lacquer. When working on windows and doors, do not use in the gasket area. When lacquer ceases to flow well, press again or touch down tip at a flat angle (about 45 degree) with light pressure. The valve opens ensuring a well-measured and constant lacquer flow.

Avoid squeezing 'P' during application, as this may result in an uncontrollable lacquer flow.

Replace cap after use.

Dried up tips can be washed out in nitrocellulose thinner. If the pen has not been used for a long time or where pigment separates at the tip, just replace with a new tip. For more details, please see instructions for use.

## Physical Properties and Shelf Life

<b>Processing:</b>	at 18-25°C and 55-65% RH
<b>Dust-dry:</b>	after approx. 1-2 minutes
<b>Touch-proof:</b>	after approx. 2-5 minutes (dependent on room temperature and layer thickness)
<b>Lightfastness:</b>	good
<b>Weather resistance:</b>	good
<b>Shelf life:</b>	minimum 2 years (stored at room temperature, in unopened original container)

## Safety Precautions

Please refer to label and material safety data sheet.

## Disposal

- Do not allow product to enter drains or watercourses.
- Non contaminated packaging may be recycled.
- Leftover material to be disposed of according to the European Waste Code 080111 – *waste paint and varnish containing organic solvents or other dangerous substances*.
- For more detailed information, please refer to the Material Safety Data Sheet for this product or ask your local waste industry office.

## Packaging

On request.

*Further information and Material Safety Data Sheet on the internet at  
[www.heinrich-koenig.de](http://www.heinrich-koenig.de)*

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).



®  
Seit 1892

**Heinrich König & Co. KG**

An der Rosenhelle 5 • D-61138 Niederdorfelden

Phone: 0 61 01-53 60 0 • Fax: 0 61 01-53 60 11

E-mail: [info@heinrich-koenig.de](mailto:info@heinrich-koenig.de)

Issue 28/16